

Technical Liquids

Lubricating and Multifunctional Oils

Thermal parameters

Temperature resistance

-25°C to +120°C

Processing

Drop or brush Bio-Fluid onto the surface to be treated.

Store in tightly closed original container. Protect from direct sunlight. The storage temperature must not exceed +50°C. Keep container in a cool, well-ventilated location. Store in dry place.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

15600001	Bio-Fluid, 1 L, transparent
15600005	Bio-Fluid, 5 L, transparent
15600010	Bio-Fluid, 10 L, transparent
15600028	Bio-Fluid, 28 L, transparent

Bio-Fluid





Highly pure mineral oil | NSF registration

WEICON Bio-Fluid is a medically pure white oil containing no resins or acids which was specially developed for lubrication and care. It is water-clear, free of solvents, odourless and tasteless, and water-repellent. It shows excellent capillary action and an NSA approval. Bio-Fluid reduces friction and wear, suppresses squeaky noises, protects against corrosion and removes dirt and rust. It can be used for the lubrication, protection and care of precision mechanisms, as a spray oil for production and filling plants, and as a lubricant for filling and packaging systems. It can be used wherever occasional, technically unavoidable contact with food or its packaging can occur. WEICON Bio-Fluid was specially developed for applications in the food and beverage industry, in the pharmaceutical and in the cosmetics industry.

Technische Daten

Silicone-free		yes
Shelf life		24 mon.
Characteristics		
Specific properties		complies with: Purity grade DAB10, USDA H1, FDA Regulations, FDA Positive List
Silicone-free		yes
Colour		transparent
Odour		nearly odourless
Viscosity index		110
Kinematic viscosity (40 °C)	DIN 51 562	70 mm²/s
Kinematic viscosity (+100 °C)	DIN 51 562	8 mm²/s
Shelf life		24 mon.



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.

Spain phone +34 (0) 914 7997 34

WEICON GmbH & Co. KG ohone +49 (0) 251 9322 0

Italy phone +39 (0) 010 2924 871

WEICON Romania SRL phone +40 (0) 3 65 730 763

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON South East Asia Pte Ltd ne (+65) 6710 7671

WEICON Kimya Sanayi Tic. Ltd. Sti Turkey phone +90 (0) 212 465 33 65